

SPARKGAS 30 W 50Hz

Code: 15680010 Series: SPARKGAS



Technical and functional features

- -Single stage operation (on/off).
- -Compatible with any type of combustion chamber.
- -Air-gas mixing at blast-pipe.
- -Ability to obtain optimal combustion values by regulating combustion air and blast-pipe.
- -Maintenance facilitated by the fact that the mixing unit can be removed without having to remove the burner from the boiler.
- -Manual air flow adjustment.
- -Possibility to chose gas train with valve tightness control.
- -Comes with a 7-poles connector, 1 flange and 1 insulating seal to connect the burner to the application.

Design features

- -Light aluminium alloy fan part.
- -High performance centrifugal fan.
- -Combustion air inlet with device to adjust the air flow.
- -Sliding boiler coupling flange to adapt the head protrusion to the various types of boilers.
- -Adjustable blast-pipe with stainless steel nozzle and deflector disk in steel.
- -Monophase electric motor to run fan.
- -Noise insulation.
- -Air pressure switch to ensure the presence of combustion air.
- -Gas train complete with operation and safety valve, minimum pressure switch, pressure regulator and gas filter.
- -Sequence controller EN 298..
- -Flame scanning by ionisation electrode.
- -Start/stop switch (except the W version).
- -7 pole outlet for burner electrical and thermostat supply.
- -Electrical plant protection rating IP40.
- -Sound-proof plastic protective cover (except the W version).

Available version on request

-Blast-pipe with greater than standard protrusion and device for air gate closure during pause to avoid loss of heat up flue.

Technical Data - SPARKGAS 30 W 50Hz:

Minimum Rated output	60	kW	
Maximum Rated output	300	kW	
Minimum gas flow rate	6	m3/h	
Maximum gas flow rate	30	m3/h	
Motor rated power	0.37	kW	
Electric Power Supply Phase	1	N	
Electric Power Supply Frequency 1	50	Hz	
Electric Power Supply Current	AC		
Electric Power Supply Voltage	230	V	
Width	460	mm	
Depth	835	mm	

Weight	22	kg
Pack Width	1010	mm
Pack Height	390	mm
Package depth	490	mm
Weight of Packaging	32	kg