



SPARK 35 W 50Hz

Code: 3070010

Series: SPARK



Technical and functional features

- Light oil burners.
- Single stage operation (on/off).
- Compatible with any type of combustion chamber.
- High pressure mechanical atomisation of fuel using nozzle.
- Ability to obtain optimal combustion values by regulating combustion air and blast-pipe.
- Maintenance facilitated by the fact that the atomisation unit can be removed without having to remove the burner from the boiler.
- Manual air flow adjustment.
- Comes with a 7-poles connector, 2 flexible oil pipes, 1 nozzle, 1 oil filter, 1 flange and 1 insulating seal to connect the burner to the application.

Design features

- Light aluminium alloy fan part.
- High performance centrifugal fan.
- Combustion air inlet with device to adjust the air flow.
- Sliding boiler coupling flange to adapt the head protrusion to the various types of boilers.
- Adjustable blast-pipe with stainless steel nozzle and deflector disk in steel.
- Monophase electric motor to run fan and pump.
- Noise insulation.
- Gear pump with pressure regulator and fuel stop-cock valve.
- Sequence controller - EN 230..
- Photoresistance flame scanner.
- 7 pole outlet for burner electrical and thermostat supply.
- Electrical plant protection rating IP40.
- Sound-proof plastic protective cover (except the W version).

Available version on request

- Blast-pipe with greater than standard protrusion, a device for air gate closure during pause to avoid loss of heat up flue, for biodiesel running.

Technical Data - SPARK 35 W 50Hz:

Minimum Rated output	178	kW
Maximum Rated output	391	kW
Minimum light oil flow rate	15	kg/h
Maximum light oil flow rate	33	kg/h
Fuel max viscosity	1.5	°E
Motor rated power	0.37	kW
Electric Power Supply Phase	1	N
Electric Power Supply Frequency 1	50	Hz
Electric Power Supply Current	AC	
Electric Power Supply Voltage	230	V
Width	450	mm

Height	372	mm
Depth	780	mm
Weight	23	kg
Pack Width	940	mm
Pack Height	390	mm
Package depth	490	mm
Weight of Packaging	30	kg