



BTL 3 50-60Hz

Code: 35450010

Series: BTL

Technical and functional features

- Light oil burners.
- Single stage operation (on/off).
- Compatible with any type of combustion chamber.
- High pressure mechanical atomisation of fuel using nozzle.
- Ability to obtain optimal combustion values by regulating combustion air and blast-pipe.
- Maintenance facilitated by the fact that the atomisation unit can be removed without having to remove the burner from the boiler.
- Manual air flow adjustment.
- Comes with a 7-poles connector, 2 flexible oil pipes, 1 nozzle, 1 oil filter, 1 flange and 1 insulating seal to connect the burner to the application.

Design features

- Light aluminium alloy fan part.
- High performance centrifugal fan.
- Combustion air inlet with device to adjust the air flow.
- Automatically closing air gate (except BTL 26).
- Sliding boiler coupling flange to adapt the head protrusion to the various types of boilers.
- Adjustable blast-pipe with nozzle and deflector disk in steel.
- Monophase electric motor to run fan and pump.
- Gear pump with pressure regulator and fuel stop-cock valve.
- Sequence controller - EN 230..
- Photoresistance flame scanner.
- 7 pole outlet for burner electrical and thermostat supply.
- Electrical plant protection rating IP40.
- Sound-proof plastic protective cover.

Available version on request

- Biodiesel operation.

Technical Data - BTL 3 50-60Hz:

Minimum Rated output	17.8	kW
Maximum Rated output	42.7	kW
Minimum light oil flow rate	1.5	kg/h
Maximum light oil flow rate	3.6	kg/h
Fuel max viscosity	1.5	°E
Motor rated power	0.09	kW
Electric Power Supply Phase	1	N
Electric Power Supply Frequency 1	50	Hz
Electric Power Supply Frequency 2	60	Hz
Electric Power Supply Current	AC	
Electric Power Supply Voltage	230	V
Width	250	mm

Height	218	mm
Depth	330	mm
Weight	8.2	kg
Pack Width	400	mm
Pack Height	280	mm
Package depth	300	mm
Weight of Packaging	9	kg