



BTL 14 50Hz

Code: 35610010

Series: BTL



Technical and functional features

- Light oil burners.
- Single stage operation (on/off).
- Compatible with any type of combustion chamber.
- High pressure mechanical atomisation of fuel using nozzle.
- Ability to obtain optimal combustion values by regulating combustion air and blast-pipe.
- Maintenance facilitated by the fact that the atomisation unit can be removed without having to remove the burner from the boiler.
- Manual air flow adjustment.
- Comes with a 7-poles connector, 2 flexible oil pipes, 1 nozzle, 1 oil filter, 1 flange and 1 insulating seal to connect the burner to the application.

Design features

- Light aluminium alloy fan part.
- High performance centrifugal fan.
- Combustion air inlet with device to adjust the air flow.
- Automatically closing air gate (except BTL 26).
- Sliding boiler coupling flange to adapt the head protrusion to the various types of boilers.
- Adjustable blast-pipe with nozzle and deflector disk in steel.
- Monophase electric motor to run fan and pump.
- Gear pump with pressure regulator and fuel stop-cock valve.
- Sequence controller - EN 230..
- Photoresistance flame scanner.
- 7 pole outlet for burner electrical and thermostat supply.
- Electrical plant protection rating IP40.
- Sound-proof plastic protective cover.

Available version on request

- Biodiesel operation.

Technical Data - BTL 14 50Hz:

Minimum Rated output	83	kW
Maximum Rated output	166	kW
Minimum light oil flow rate	7	kg/h
Maximum light oil flow rate	14	kg/h
Fuel max viscosity	1.5	°E
Motor rated power	0.18	kW
Electric Power Supply Phase	1	N
Electric Power Supply Frequency 1	50	Hz
Electric Power Supply Current	AC	
Electric Power Supply Voltage	230	V
Width	303	mm
Height	345	mm

Depth	620	mm
Weight	17	kg
Pack Width	780	mm
Pack Height	410	mm
Package depth	370	mm
Weight of Packaging	18	kg