



GI MIST 510 DSPGM CE 50Hz

Code: 6681050

Series: GI MIST DSPGM

Technical and functional features

- Dual fuel natural gas/light oil burners..
- Two-stage progressive output operation.
- Ability to operate with output modulation by means of automatic RWF40 regulator mounted on the control panel (order separately with the specific modulation kit).
- Compatible with any type of combustion chamber.
- Air-gas mixing at blast-pipe and high pressure mechanical atomisation of fuel using nozzle.
- Ability to obtain optimal combustion values by regulating combustion air and blast-pipe.
- Maintenance facilitated by the fact that the mixing unit and the atomisation unit can be removed without having to remove the burner from the boiler.
- Minimum and maximum air flow regulation for first and second stage by means of electric servomotor with pause closure of gate to prevent any heat dispersion to flue.
- Tightness gas valve control, EN676.
- Equipping for automatic fuel switching.

GI MIST 350 - 420 - 510 DSPGM

- Comes with 2 flexible oil pipes, 1 oil filtre, 1 flange and 1 insulating seal to connect the burner to the application. Nozzle must be ordered separately according to the burner nominal output required..

GI MIST 1000 DSPGM

- Comes with 2 flexible oil pipes, 1 oil filtre, 1 flange and 1 insulating seal to connect the burner to the application. Nozzle must be ordered separately according to the burner nominal output required..

Design features

- High performance centrifugal fan.
 - Combustion air inlet with device to adjust the air flow.
 - Adjustable blast-pipe with stainless steel nozzle and deflector disk in steel.
 - A three-phase electric motor to run fan and another to run the pump.
 - Air pressure switch to ensure the presence of combustion air.
 - Electric servomotor with mechanical cam for simultaneous regulation of combustion air and fuel.
 - Gear pump with pressure regulator.
 - Atomisation unit with magnet to control the outlet/nozzle return pins.
 - Sequence controller - EN 298..
 - Ultra Violet cel flame scanner.
 - Terminal block for the electrical and thermostatic connections to the burner and to control the second stage of working or for the connection of the electronic output regulator.
 - Electrical plant protection rating IP40.
- GI MIST 350 - 420 - 510 DSPGM
- Light aluminium alloy fan part.
 - Sliding boiler coupling flange to adapt the head protrusion to the various types of boilers.
 - Gas train complete with control, operating, safety and pilot valves, valve seal control, minimum and maximum pressure switch, pressure control and gas filter.
 - Control panel comprising stop/go switch, automatic/manual and minimum/maximum selector, fuel change switch and operation, block and fuel used indicator.

GI MIST 1000 DSPGM

-Steel fan part.

-Flange for connection with generator anchored with hinge for easy dismantling of spray nozzle unit and flame disc.

-Main gas train complete with control, operating, safety and pilot valves, valve seal control, minimum and maximum pressure switch, pressure control and gas filter.

-Burner ignition gas train complete with operating and safety valve, minimum pressure switch, pressure control and gas filter.

-On board derivation box and remote control panel including:Start/stop switch.Automatic/manual and minimum/maximum selector.Fuel selector switch.On, shutdown and fuel consumed indicator lights.

Technical Data - GI MIST 510 DSPGM CE 50Hz:

Minimum Rated output	2430	kW
Maximum Rated output	6500	kW
Minimum light oil flow rate	205	kg/h
Maximum light oil flow rate	548	kg/h
Minimum gas flow rate	244	m3/h
Maximum gas flow rate	654	m3/h
Fuel max viscosity	1.5	°E
Motor rated power	21.5	kW
Electric Power Supply Phase	3	N
Electric Power Supply Frequency 1	50	Hz
Electric Power Supply Current	AC	
Electric Power Supply Voltage	400	V
Width	1345	mm
Height	1540	mm
Depth	2030	mm
Weight	610	kg
Pack Width	2270	mm
Pack Height	1250	mm
Package depth	1600	mm
Weight of Packaging	700	kg