



BGN 300 LX V 50Hz

Code: 15270015

Series: BGN LX

Technical and functional features

- Low NOx and CO gas-fired burners, EN676 "Classe III".
- Two-stage progressive output operation.
- Ability to operate with output modulation by means of automatic RWF40 regulator mounted on the control panel (order separately with the specific modulation kit).
- Compatible with any type of combustion chamber.
- Air-gas mixing at blast-pipe.
- Burnt gas recycling blast-pipe able to achieve very low pollutant emissions, particularly with regard to nitrous oxides (NOx).
- Ability to obtain optimal combustion values by regulating combustion air and blast-pipe.
- Maintenance facilitated by the fact that the mixing unit can be removed without having to remove the burner from the boiler.
- Minimum and maximum air flow regulation for first and second stage by means of electric servomotor with pause closure of gate to prevent any heat dispersion to flue.
- Fan speed adjustment in relation to changes in burner demand provided by means of inverter, to obtain a significant reduction in noise levels and electricity consumption (version V only).
- Tightness gas valve control, EN676.
- Comes with 1 flange and 1 insulating seal to connect the burner to the application.

Design features

- Light aluminium alloy fan part.
- High performance centrifugal fan.
- Combustion air inlet with device to adjust the air flow.
- Sliding boiler coupling flange to adapt the head protrusion to the various types of boilers.
- Adjustable blast-pipe with stainless steel nozzle and deflector disk in steel.
- Three-phase electric motor to run fan (controlled electronically by means of a motor speed controller in "V" execution).
- Air pressure switch to ensure the presence of combustion air.
- Monoblock modulating gas train complete with operation and safety valve, valves seal control, minimum pressure switch, pressure regulator and gas filter.
- Sequence controller - EN 298..
- Flame scanning by ionisation electrode.
- Control panel comprising stop/go switch, automatic/manual and minimum/maximum selector, operation and block indicator.
- Terminal block for the electrical and thermostatic connections to the burner and to control the second stage of working or for the connection of the electronic output regulator.
- Electrical plant protection rating IP40.

Technical Data - BGN 300 LX V 50Hz:

Minimum Rated output	400	kW
Maximum Rated output	3600	kW
Minimum gas flow rate	40	m ³ /h
Maximum gas flow rate	362	m ³ /h
Motor rated power	7.5	kW
Electric Power Supply Phase	3	N

Electric Power Supply Frequency 1	50	Hz
Electric Power Supply Current	AC	
Electric Power Supply Voltage	400	V
Width	845	mm
Depth	1740	mm
Weight	245	kg
Pack Width	2030	mm
Pack Height	990	mm
Package depth	1210	mm
Weight of Packaging	317	kg